



U2

Universal suction cup

- Suitable for objects with flat or slightly curved surfaces.
- Also used for concave objects.
- Suction cups of conductive silicone are suitable for objects with sensitivity to static electricity.

Lifting	forces	Q,	Technical	data
Lituita	101 Ces	α	recrimical	uala


Outer Dia		orce vertical lbf, at vacuu		_	rce parallel bf, at vacuu		Volume	Min. curve radius	Max. vertical movement	Weight rubber part
in	6 -inHg	18 -inHg	27 -inHg	6 -inHg	18 -inHg	27 -inHg	in ³	in	in	OZ
0.10	0.007	0.02	0.03	_	_	_	0.0002	0.16	0.004	0.0004

Material specifications				
Material	Color	Hardness °Shore A	Temperature range °F	
Conductive silicone, CSII	Black	50	67-446	


Material res	istance							
Wear resistance	Oil	Weather & Ozone	Hydrolysis	Gasoline	Concentrated acids	Alcohol	Oxidation	
Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent	1

Ordering information

Suction cups with fitting	Weight (oz)	Part No.
Suction cup U2 Conductive silicone, M2.5 male	0.0184	U2.25.01AA



Rubber parts	Part No.
Suction cup U2 Conductive silicone	U2.25



Fittings	Part No.
Fitting M2.5 male	01AA