





B75-2

Suction cup with short bellows and filter disk

- Suitable for level adjustment. Several short bellows in one lifting device can handle objects with height differences and varying shapes, for example embossed or corrugated plates.
- Lifting movement to separate small and thin objects.
- Only lightweight objects should be handled when the lifting force is parallel to the surface of the object, in order to achieve good precision and safe lifting movement.
- Filter disk made of PE.

Lifting forces & Technical data

Outer Dia.	3	ng force vertical to the Lifting force para- face, lbf, at vacuum level surface, lbf, at va		•		Volume	Min. curve radius	Max. vertical movement	Weight rubber part	
in	6 -inHg	18 -inHg	27 -inHg	6 -inHg	18 -inHg	27 -inHg	in ³	in	in	oz
3.07	16.6	37.5	50.8	_	_	_	6.70	1.60	0.94	1.23

Material	specifications


Material	Color	Hardness °Shore A	Temperature range °F
Nitrile-PVC, NPV	Black	50	32–194*
Silicone, SIL	Red	50	-40–392*
*Filter disk max. 176°F			

Material resistance


Material	Wear resistance	Oil	Weather & Ozone	Hydrolysis	Gasoline	Concentrated acids	Alcohol	Oxidation
Nitrile-PVC, NPV	Excellent	Excellent	Good	Good	Excellent	Fair	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent

Ordering	information
----------	-------------

Oit	ering information		
	Suction cups with fitting	Weight (oz)	Part No.
Α	Suction cup B75-2 Nitrile-PVC, 1/8" NPSF female AI, with mesh filter	3.22	B75-2.30.07UA
Α	Suction cup B75-2 Nitrile-PVC, 3/8" NPSF female AI, with mesh filter	3.79	B75-2.30.07UB
Α	Suction cup B75-2 Nitrile-PVC, G1/2" female AI, with mesh filter	3.66	B75-2.30.07UD
Α	Suction cup B75-2 Nitrile-PVC, $1/4$ " NPT female AI, with mesh filter & 10-32 addl. conn.	3.94	B75-2.30.07UH
В	Suction cup B75-2 Nitrile-PVC with filter, 1/8" NPSF female, with mesh filter	3.63	B75-2.30.07NA
В	Suction cup B75-2 Nitrile-PVC with filter, G3/8" female, with mesh filter	3.63	B75-2.30.07ND
В	Suction cup B75-2 Nitrile-PVC with filter, 3/8" NPSF female, with mesh filter	3.63	B75-2.30.07NE
В	Suction cup B75-2 Nitrile-PVC with filter, G1/2" female, with mesh filter	3.63	B75-2.30.07NF
Α	Suction cup B75-2 Silicone, 1/8" NPSF female AI, with mesh filter	3.22	B75-2.20.07UA
Α	Suction cup B75-2 Silicone, 3/8" NPSF female AI, with mesh filter	3.79	B75-2.20.07UB
Α	Suction cup B75-2 Silicone, G1/2" female AI, with mesh filter	3.67	B75-2.20.07UD
Α	Suction cup B75-2 Silicone, $1/4$ " NPT female AI, with mesh filter & 10-32 addl. conn.	3.94	B75-2.20.07UH
В	Suction cup B75-2 Silicone with filter, 1/8" NPSF female, with mesh filter	3.63	B75-2.20.07NA
В	Suction cup B75-2 Silicone with filter, G3/8" female, with mesh filter	3.63	B75-2.20.07ND
В	Suction cup B75-2 Silicone with filter, 3/8" NPSF female, with mesh filter	3.63	B75-2.20.07NE
В	Suction cup B75-2 Silicone, G1/2" female, with mesh filter	3.63	B75-2.20.07NF



Rubber parts	Part No.
Suction cup B75-2 Nitrile-PVC, with filter	B75-2.30
Suction cup B75-2 Nitrile-PVC, with filter & washer	B75-2.30.W
Suction cup B75-2 Silicone, with filter	B75-2.20
Suction cup B75-2 Silicone, with filter & washer	B75-2.20.W



Description	Part No.
Fitting 1/8" NPSF female AI, with mesh filter	07UA
Fitting 3/8" NPSF female AI, with mesh filter	07UB
Fitting G1/2" female AI, with mesh filter	07UD
Fitting 1/4" NPT female AI, with mesh filter & 10-32 addl. conn.	07UH
Fitting 75, 1/8" NPSF female, clamp ring with mesh filter	07NA
Fitting 75, G3/8" female, clamp ring with mesh filter	07ND

Fitting 75, 3/8" NPSF female, with mesh filter	07NE
Fitting 75, G1/2" female, clamp ring with mesh filter	07NF

Spare part	Material	Temperature range °F	Part No.
Filter D=80, 10 pcs, for B75-2	Polyethylene, PE	-40–176	02.01.149